

12-inch 75mm Midbass Driver SML127527



Features:

1. Excellent chemical stability

High sound pressure, strong shock, high sensitivity, small volume and small distortion

2. Use high penetration carbon fiber dust cap

High performance fibre dust cap is used in this unit. It strengthen the rigidity and toughness of the speaker and makes the voice clearer. High Neodymium Magnet U iron models use Nd-Fe-B 40SH magnet, high density and strong magnetism, which is conducive to better sound explosion.

3. Audio Experience, Shock Sounding

The 75-core U-iron roundness performances speaker retains the original sound, greatly reduces the distortion rate, and the bass is strong and powerful.

4. Imported loosely pressed edged paper basin

DuPont 75 core high temperature resistant pure aluminium wire voice coil, 24 strands of high strength braided line, use imported loosely pressed edged paper basin, Moisture-proof, corrosion-proof and oxidation-proof, effectively enhance the service life of speaker at high power.

12-inch 75mm Midbass Driver



Model: SML127527



Specification:

Model	SML127527
Description	12-inch 75-core midbass speaker
Installation aperture	About 282mm
Diagonal screw hole	About 298mm
Height	About 152mm
Magnet	NdFeB 131 magnetism
Frame material	Cast aluminum frame
Rated Impedance	8 ohm
DC Impedance	6 ohm
Rated Power	350 Watts
Maximum power	700 Watts
Sensitivity	97.5 dB/1W/1m
Frequency range	40-3K Hz
Resonant frequency	54Hz
Electrical Quality Factor Number	0.36
Mechanical Quality Factor Value	7.7
Total Quality Factor Number	0.34
Effective Volume	54 liters
Vibration Area	522.0cm ²
Magnetic Force	18.9 Txm
Effective Mobile Quality	67g
Place of Origin	Guangzhou, China
Net Weight	About 5.4KG (Include packaging)

Good products should talk with data

