

15-inch 100mm Midbass Driver SML1510060



Features:

1. 15-inch new loud bass

High sensitivity, excellent for instantaneous response and auditory details

2. Let you feel thunderous shock

The elastic wave is made of Dupont blended fabric, transverse rigid balance, accurate positioning.

3. Professional high-power plum blossom magnet

High-quality terminal to ensure long-term stable signal output break off transmission and resulting high-pitched whistle

4. Strengthened and thickened Aluminum basin frame

High quality thickened Aluminum basin frame effectively guaranteeing the stability of low frequency in large dynamic bass. Lengthened screw installation hole design suitable for most audio thread hole positions. Design basin frame according to professional acoustics to ensure heavy, stable and high reducibility of low-frequency vibration.

15-inch 100mm Midbass Driver



Model: SML1510060



Specification:

Model	SML1510060
Description	15-inch 100-core midbass speaker
Installation aperture	About 355mm
Diagonal screw hole	About 375mm
Height	About 200mm
Magnet material	Granular magnetism
Frame material	Cast aluminum frame
Rated Impedance	8 ohm
DC Impedance	6 ohm
Rated Power	600 Watts
Maximum power	1.2K Watts
Sensitivity	97.5 dB/1W/1m
Frequency range	40-3K Hz
Resonant frequency	40Hz
Electrical Quality Factor Number	0.32
Mechanical Quality Factor Value	5.4
Total Quality Factor Number	0.30
Effective Volume	177 liters
Vibration Area	866.0cm ²
Magnetic Force	19.5 Txm
Effective Mobile Quality	192g
Place of Origin	Guangzhou, China
Net Weight	About 9.3KG (No packaging)

Good products should talk with data

