

LD Series Interactive LED Display SP-SLD86



Description:

LD series Interactive LED Display has the leading infrared touch technology, with the perfect touch effect and advanced HID plug and play technology. All series with the A+ standard screen with the size from 55",65" 70" 75" to 86".

Features:

1. HD Display and Beautiful Color
2. Exquisite Craft, Excellent Experience
3. Modular Industrial Design

Exquisite craft, Excellent Experience



Modular Industrial Design



Specification:

| | |
|---------------------------------|--|
| Model | SP-SLD86 |
| Physical Size | 86 inch |
| Effective Size | 1922*1093mm |
| Display Ratio | 16:9 |
| Physical Dimension | 1992*1210*114mm |
| Packing Size | 2180*1450*280mm |
| Net Weight | 126 KG |
| Gross Weight | 150 KG |
| Induction Technology | Infrared |
| Induction Object | Finger, pen or untransparent object |
| Resolution | 32768(W) * 32768(D) |
| Calibration Deviation | <2mm |
| Tracking Speed | >200inch/sec |
| Cursor Speed | Max 300dots/sec |
| Effective Touch Object | >=∅ 8mm |
| Mouse Function | Single click, double click, right click |
| Responding Speed | 15ms |
| Consequent RS | 8ms |
| Life | 100000hrs |
| Voltage | DC 5.0V +- 5% |
| Touchscreen Power Supply | USB |
| Power Consumption | <=160W(200mA DC 5V) |
| CPU | Pentium 800 (1G Hz (X86) CPU or above) |
| Memory | 1GB or above |
| Hard disk | >=800mb |
| Operation System | Windows 2000, Windows XP, Window Vista, Windows7, Windows 8.1, Windows10, Linux, Mac, Android |
| Working Temperature | 30℃ ~ 60℃ |
| Working Humidity | 0% ~ 95% |
| Working Environment | Indoor / Outdoor |
| Packing Details | Interactive LED Display *1; Software Disc *1; Whiteboard PEN *2; User Manual *1; Warranty Card *1; 5M USB *1; Wall-mount Suit *1 |
| Place of Origin | Guangzhou, China |